PROTECTION FACTOR TESTING OF THE
3M BREATHE EASY (BE-10) POWERED AIR PURIFYING RESPIRATOR (PAPR)

Adam D. Seiple
Alex G. Pappas

ENGINEERING DIRECTORATE

8 May 2003

Disclaimer

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorizing documents.

REPORT DOCUMENTATION PAGE		Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.		

1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE 2003 May	3. REPORT TYPE AND DATES COVERED Final; 01 Dec

4. TITLE AND SUBTITLE PROTECTION FACTOR TESTING OF THE 3M BREATHE EASY (BE-10) POWERED AIR PURIFYING RESPIRATOR (PAPR)	5. FUNDING NUMBERS None
6. AUTHOR(S) Adam D. Seiple, Alex G. Pappas	

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) TECH DIR, ECBC, ATTN: AMSSB-REN-SN, APG, MD 21010-5424	8. PERFORMING ORGANIZATION REPORT NUMBER ECBC–TR-
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) TECH DIR, ECBC, ATTN: AMSSB-RTD, APG, MD 21010-5424	10. SPONSORING/MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.	12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Results of performance testing of the 3M Breathe Easy (BE-10) PAPR is described. A series of tests were performed to determine the corn-oil protection factors using human subjects.

14. SUBJECT TERMS Corn oil Aerosol PAPR Respirator Cartridge Protection Factor (PF) Testing		15. NUMBER OF PAGES 24
		16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. Z39-18
298-102

Blank

Executive Summary

The work described in this report was authorized under the **TSA Project No. 209** for the U.S. Army Soldier and Biological Chemical Command (SBCCOM). This work was conducted during December 2001 and includes information contained in an earlier report under the Domestic Preparedness Evaluation Program. Protection Factor (PF) testing of the Improved 3M BE-10 PAPR was completed on December 15, 2001 at the Mask Fit Test Facility using 24 different military volunteers. The BE-10 PAPRs were pre-screened on the TDA-99M prior to PF testing to determine quality. All 12 PAPRs passed this testing while on the Smartman and being breathed at 25 liter per minute. The purpose of this testing (the TDA testing and the PF testing) was to see if the 3M BE-10 PAPR could be used by a civilian/First Responder population in the event of a chemical or biological terrorist attack.

Each volunteer performed five trials of 10 one-minute exercises while wearing the 3M BE-10 PAPR. Air sampling occurred at the oro-nasal region. Two methods of oro-nasal sampling were used: Standard U.S. Army oro-nasal sample and 3M oro-nasal cannula sample. After performing several tests it became evident that the Army method was less labor intensive and showed no significant difference with the 3M method. 3M representatives agreed to continue sampling only with the U.S. Army method.

Precise PF values were calculated for each exercise by an instrument called a Laser Photometer (rear light-scattering). The instrument can measure leakage into the mask by shining a laser over the cross-sectional area of the sample. If corn oil is present, the laser will refract and register a voltage peak. This voltage peak is then compared to the chamber reading and converted by the instrument into a PF value.

Since this civilian mask is a PAPR, the U.S. Army requires that it meet 100% pass rates at the 10000 PF level. The 3M BE-10 PAPR met and surpassed this requirement achieving 100% pass rates at the 10000 and 20000 PF levels, respectively.

Blank

PREFACE

The work described in this report was authorized under the **TSA Project No. 209** for the U.S. Army Soldier and Biological Chemical Command (SBCCOM) The use of either trade or manufacturers' names in this report does not constitute an official endorsement of any commercial products. This report may not be cited for purposes of advertisement.

This report has been approved for public release. Registered users should request additional copies from the Defense Technical Information Center; unregistered users should direct such requests to the National Technical Information Service.

Blank

TABLE OF CONTENTS

Blank

PROTECTION FACTOR TESTING OF THE 3M BREATHE EASY (BE-10) POWERED AIR PURIFYING RESPIRATOR (PAPR)

1.0   Introduction

The 3M Breathe Easy (BE-10) PAPR was tested to determine its capability to protect first responders, i.e. firemen and policemen, from a chemical or biological attack. The complete unit includes the blower/filtration unit, appropriate respirator headpiece assembly, breathing tube assembly, rechargeable battery and appropriate filters. The PAPR is designed to protect the wearer from airborne contaminants (particulates such as dusts, mists and fumes), organic vapors, acid gases, and other inorganic gases. It is specifically designed not to handle atmospheres containing less than 19.5 % oxygen and contaminant concentrations above Immediately Dangerous to Life and Health (IDLH) levels. Testing was conducted through a test service agreement (TSA) between the 3M Company and the US Army Edgewood Chemical Biological Center.

2.0 Background

The BE10 was originally marketed by RACAL as the BE20. Earlier testing, as part of the Domestic Preparedness (DP) Program, indicated there might be a problem with leakage around the exhalation valve. The valves of the BE10 and BE20 were compared and it was found that there is a difference in the design of the ring nut that secures the valves to the PAPR lens.   Edgewood Chemical Biological Center (ECBC) personnel considered this as a possible leak point. There was also concern about a flashing problem that occurred in the blower housing where the filter cartridges are mounted. 3M provided a gasket to ECBC as a mod kit and a gasket for the ring nut. The PAPR was subsequently retested. This report discusses the second Protection Factor (PF) test performed on this PAPR.

3.0   Objective

The PF test used a corn oil aerosol to simulate chemical and biological airborne agents. Human subjects wore the 3M BE-10 PAPR inside the corn oil aerosol chamber to determine the device's overall PF.

4.0   Protection Factor Testing

4.1   Testing Facilities

Testing occurred in Building E5604, Aberdeen Proving Grounds – Edgewood Area, MD 21010 on Saturday, December 15, 2001. A challenge aerosol concentration of

20 - 40 mg/m³, polydispersed corn oil aerosol having a mass median aerodynamic diameter (MMAD) of 0.4 to 0.6 μm (the Army Standard) was generated in a 10-ft × 20-ft × 32-ft test chamber. The test chamber challenge aerosol was generated by atomizing liquid corn oil at room temperature using a Laskin nozzle. The Laskin nozzle produced a coarse aerosol cloud, which was directed into an impaction plate to remove the larger particles and yield an aerosol in the desired size range. The concentrated aerosol from the generator was diluted with filtered ambient air to control the challenge aerosol concentration in the exposure chamber.

A 6-decade, 45 degree off-axis light-scattering laser photometer, sampling at a flow rate of $1 - 2$ L/min, was used to quantify concentration of the challenge and the in-mask corn oil aerosols. For a given particle size, the quantity of scattered light is proportional to the aerosol concentration. The photometer converted the quantity of scattered light to a voltage, which was then digitized and recorded by a microcomputer.

4.2 Preparation of Test Items

A total of 12 3M BE-10 PAPR units were received at the PF Testing Facility for use in the test. All units were then checked for quality with a TDA-99M. The units were configured with a SMARTMAN breathing at 25 liters per minute. All units passed this prescreening process.

A sample port must be fitted somewhere in the unit so it can connect to the laser photometers. It was initially decided that 3M cannula probes were going to be used in the oro-nasal region. After the first few trials, this probe became too labor intensive and it was determined by ECBC personnel and 3M representatives that US Army oro-nasals probes were just as adequate. The U.S. Army standard probes were used from this point forward.

4.3 Test Procedure

On test day, 24 military volunteers were chosen for the test. Upon their arrival at the testing facility, some anthropometrical data was taken from them including facial length, facial width and head breadth. This data can be found in Appendix A. ECBC personnel then went over an orientation for the volunteers, which explained the test and a volunteer agreement for each volunteer to sign.

The volunteers were then trained on the 3M BE-10 PAPR and how it should be donned properly. Once ready, a group of 8 volunteers prepared to enter the chamber. They were expertly donned with the 3M BE-10 PAPR units by 3M representatives and were instructed to enter the chamber.

Once inside the chamber the volunteers were instructed to complete the following ten one-minute exercises to stress the seal of the mask:

Normal Breathing
Deep Breathing
Move Head Side to Side
Move Head Up and Down
Recite the "Rainbow" Passage
Sight the Rifle
Reach for the Floor and Ceiling
On Hands and Knees, Look Left and Right
Facial Expressions
Normal Breathing

Once all exercises were completed the volunteers were instructed to exit the chamber. They then removed the equipment and completed a comfort survey. That complete cycle is considered 1 trial. Each volunteer completed 5 trials for a total of 120 trials for the complete test.

5.0 Data Analysis

The PAPR's performance was quantified in terms of a protection factor (PF). The PF was calculated by determining the ratio of the challenge aerosol concentration to the in-mask aerosol concentration as quantified by integrating the peak voltage output from the photometer over a time interval. A PF was calculated for each individual exercise (PF_i):

$$PF_i = \frac{Challenge\,Concentration}{In-mask\,Concentration}$$

Each PF_i for that trial were then used to calculate an overall PF for a volunteer (PF_o) as follows:

$$PF_o = n\left(\sum_{i=1}^{n}\frac{1}{PF_i}\right)^{-1}$$

Where n is the number of exercises. The PF_o is affected most by the smallest PF_i. Under the conditions of this test and the sensitivity of the photometer, the maximum PF that can be reported is 100,000. In Appendix B, the PF_i is listed under each exercise and the PF_o is listed under Average Fit (AVEFIT).

6.0 Results and Discussion

The test data are summarized below in Tables 1 and 2. Table 1 represents the 2 trials done with the 3M cannula probe while Table 2 shows the results from the remaining trials using the U.S. Army oro-nasal probe. The first column lists each range of PF computed. The second column is the number of test trials falling within each calculated PF range. The third column presents the cumulative-percentage of test trials that resulted in a PF below the upper limit of the range and the fourth column presents the percentage of trials that exceed the lower limit of the range shown.

Table 1 – Trials using cannulus probes

PF	Frequency	Cumulative %	Pass %
0.0	0	.00%	100.0%
10.0	0	.00%	100.0%
50.0	0	.00%	100.0%
100.0	0	.00%	100.0%
200.0	0	.00%	100.0%
500.0	0	.00%	100.0%
1000.0	0	.00%	100.0%
1667.0	0	.00%	100.0%
2000.0	0	.00%	100.0%
5000.0	0	.00%	100.0%
6667.0	0	.00%	100.0%
10000.0	0	.00%	100.0%
20000.0	0	.00%	100.0%
50000.0	0	.00%	100.0%
100000.0	4	100.00%	0.0%

Table 2 – Trials using U.S. Army standard probes

PF	Frequency	Cumulative %	Pass %
0.0	0	.00%	100.0%
10.0	0	.00%	100.0%
50.0	0	.00%	100.0%
100.0	0	.00%	100.0%
200.0	0	.00%	100.0%
500.0	0	.00%	100.0%
1000.0	0	.00%	100.0%
1667.0	0	.00%	100.0%
2000.0	0	.00%	100.0%
5000.0	0	.00%	100.0%
6667.0	0	.00%	100.0%
10000.0	0	.00%	100.0%
20000.0	0	.00%	100.0%
50000.0	6	5.36%	94.6%
100000.0	106	100.00%	0.0%

Since this civilian mask is a PAPR, the U.S. Army requires that it meet 100% pass rates at the 10000 PF level. The 3M BE-10 PAPR met and surpassed this requirement achieving 100% pass rates at the 10000 and 20000 PF levels, respectively. A major problem encountered in this testing was the battery on the PAPR. If not properly attached to the waist belt, it is easily disconnected and falls off. Three test subjects dropped their batteries during testing and that data was eliminated from the final analysis.

APPENDIX A

Anthropometrical Data

Subject	Face		Head Breadth (mm)
	Length (mm)	Width (mm)	
1	122	134	190
2	119	137	194
3	123	133	198
4	111	124	187
5	120	146	191
6	132	145	203
7	123	136	203
8	115	137	190
9	119	146	199
10	120	150	203
11	122	140	204
12	130	137	201
13	113	131	199
14	129	146	198
15	110	129	193
16	108	135	183
17	127	143	207
18	111	124	176
19	127	147	196
20	129	135	186
21	122	152	208
22	126	144	207
23	111	131	192
24	121	136	185

APPENDIX B

Raw Data

							EXERCISES									
DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	1	2	3	4	5	6	7	8	9	10
12/15/2001	10:42:12	3M-1	1	1	1	69733.9	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	18725.8	100000.0	100000.0	100000.0
12/15/2001	11:55:35	3M-9	1	1	2	43850.9	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	7681.5	55983.0	100000.0	100000.0
12/15/2001	12:55:32	3M-11	1	1	3	78879.2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	27191.6	100000.0	100000.0	100000.0
12/15/2001	14:04:24	3M-3	1	1	4	74803.3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	25375.3	70049.3	100000.0	100000.0
12/15/2001	15:01:12	3M-6	1	1	5	80584.3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	29331.0	100000.0	100000.0	100000.0
12/15/2001	10:42:13	3M-2	2	1	1	62393.6	64584.0	69841.9	75465.0	79476.9	77258.6	84783.0	26381.8	62246.6	78840.2	75497.1
12/15/2001	12:55:33	3M-12	2	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:04:25	3M-2	2	1	4	64111.7	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	64978.7	16504.9	100000.0	100000.0
12/15/2001	15:01:14	3M-2	2	1	5	74575.9	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	22680.1	100000.0	100000.0	100000.0
12/15/2001	10:42:15	3M-3	3	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:55:37	3M-6	3	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:55:34	3M-9	3	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:04:26	3M-10	3	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:01:15	3M-9	3	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	10:42:16	3M-4	4	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:55:38	3M-1	4	1	2	99922.7	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	99232.2	100000.0	100000.0	100000.0
12/15/2001	12:55:36	3M-6	4	1	3	93484.8	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	62243.6	100000.0	92384.2	99216.3
12/15/2001	14:04:27	3M-6	4	1	4	92501.9	100000.0	100000.0	100000.0	98690.6	100000.0	86729.6	83147.9	85338.1	91706.6	84789.9
12/15/2001	15:01:16	3M-11	4	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0

Concept 1 – Army Standard Probe
Concept 2 – Cannulus Probe

DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	EXERCISES									
							1	2	3	4	5	6	7	8	9	10
12/15/2001	15:41:23	3M-5	5	1	1	29837.8	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	8665.0	7156.2	100000.0
12/15/2001	15:41:23	3M-10	5	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-3	5	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-9	5	1	4	28870.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	40097.5	4572.5	30542.2	100000.0
12/15/2001	15:41:23	3M-1	5	1	5	86332.6	90847.7	100000.0	85244.2	87833.1	84414.7	85151.2	80333.0	63819.9	100000.0	100000.0
12/15/2001	15:41:23	3M-6	6	1	1	58164.6	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	12206.2	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-2	6	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-2	6	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	6	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-10	6	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	7	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-11	7	1	2	71515.4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	20068.2	100000.0	100000.0
12/15/2001	15:41:23	3M-8	7	1	3	56733.3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	11592.4	100000.0	100000.0
12/15/2001	15:41:23	3M-4	7	1	4	43023.7	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	7021.0	100000.0	100000.0
12/15/2001	15:41:23	3M-14	7	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-8	8	1	1	57202.5	50579.3	45573.3	49941.0	57603.1	59198.3	62045.3	61888.0	66286.6	64391.8	62750.0
12/15/2001	15:41:23	3M-4	8	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-10	8	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-8	8	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-5	8	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0

Concept 1 – Army Standard Probe
Concept 2 – Cannulus Probe

DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	EXERCISES 1	2	3	4	5	6	7	8	9	10
12/15/2001	12:15:26	3M-6	9	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	13:15:09	3M-8	9	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:22:29	3M-4	9	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:19:19	3M-10	9	1	5	85637.1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	37352.7	100000.0	100000.0	100000.0
12/15/2001	11:10:47	3M-9	9	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:15:27	3M-2	10	1	2	58222.8	100000.0	100000.0	92134.8	100000.0	100000.0	100000.0	16393.4	34894.0	88953.5	100000.0
12/15/2001	13:15:11	3M-12	10	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:22:30	3M-2	10	1	4	99911.1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	99118.5	100000.0	100000.0
12/15/2001	15:19:21	3M-4	10	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:10:48	3M-10	10	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:15:28	3M-3	11	1	2	59599.2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	16433.5	37124.9	100000.0	100000.0
12/15/2001	13:15:12	3M-9	11	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:22:31	3M-3	11	1	4	92118.4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	53891.2	100000.0	100000.0	100000.0
12/15/2001	15:19:22	3M-3	11	1	5	71863.6	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	42332.7	28145.1	100000.0	100000.0
12/15/2001	11:10:49	3M-11	11	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:15:29	3M-10	12	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	13:15:13	3M-10	12	1	3	90655.2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	49241.5	100000.0	100000.0
12/15/2001	14:22:32	3M-10	12	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:19:23	3M-11	12	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:10:50	3M-12	12	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0

Concept 1 – Army Standard Probe
Concept 2 – Cannulus Probe

DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	EXERCISES									
							1	2	3	4	5	6	7	8	9	10
12/15/2001	15:41:23	3M-5	13	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-5	13	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-1	13	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-8	13	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-1	13	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	14	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	14	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-11	14	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-5	14	1	5	95250.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	66724.8	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-8	15	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-1	15	1	3	55263.6	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	10994.9	100000.0
12/15/2001	15:41:23	3M-5	15	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	15	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-6	15	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-12	16	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-4	16	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-12	16	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-12	16	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-5	16	2	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0

Concept 1 – Army Standard Probe

Concept 2 – Cannulus Probe

DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	EXERCISES									
							1	2	3	4	5	6	7	8	9	10
12/15/2001	11:35:42	3M-2	17	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:35:37	3M-5	17	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	13:45:50	3M-12	17	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:41:56	3M-12	17	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:19	3M-5	17	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:35:43	3M-8	18	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	12:35:38	3M-7	18	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	13:45:51	3M-1	18	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:21	3M-12	18	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:35:44	3M-4	19	1	1	97592.2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	80210.7	100000.0	100000.0	100000.0
12/15/2001	12:35:40	3M-12	19	1	2	89660.4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	46442.5	100000.0	100000.0	100000.0
12/15/2001	13:45:52	3M-5	19	1	3	77008.1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	25090.1	100000.0	100000.0	100000.0
12/15/2001	14:41:58	3M-2	19	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:22	3M-4	19	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	11:35:45	3M-7	20	1	1	69289.1	92846.0	95803.5	96549.0	100000.0	93165.5	99054.3	24261.1	49858.9	100000.0	93870.5
12/15/2001	12:35:41	3M-6	20	1	2	95207.8	100000.0	92565.0	97327.4	100000.0	100000.0	100000.0	93932.2	83653.1	92137.0	95219.0
12/15/2001	13:45:53	3M-10	20	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	14:41:59	3M-11	20	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	20	1	5	84841.1	99192.2	88071.3	86615.7	89553.7	90383.6	92673.6	88918.8	62558.4	73429.5	90780.8

Concept 1 – Army Standard Probe
Concept 2 – Cannulus Probe

							EXERCISES									
DATE	TIME	MASK	SUBJ	CNCPT	TRIAL	AVEFIT	1	2	3	4	5	6	7	8	9	10
12/15/2001	15:41:23	3M-5	21	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-9	21	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-2	21	1	3	98262.4	100000.0	100000.0	100000.0	94739.3	100000.0	100000.0	100000.0	100000.0	94764.9	93803.6
12/15/2001	15:41:23	3M-6	21	1	4	51084.8	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	9456.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-6	21	1	5	72813.9	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	21125.4	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-11	22	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-4	22	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-6	22	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-7	22	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-1	22	1	5	78586.8	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	26847.2	100000.0
12/15/2001	15:41:23	3M-12	23	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-1	23	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-11	23	1	3	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-8	23	1	4	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-2	23	1	5	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-10	24	1	1	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-11	24	1	2	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-3	24	1	3	43179.0	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	7062.4	100000.0	100000.0	100000.0
12/15/2001	15:41:23	3M-9	24	1	5	33596.9	100000.0	100000.0	100000.0	100000.0	100000.0	100000.0	4912.8	70941.9	100000.0	100000.0

Concept 1 – Army Standard Probe

Concept 2 – Cannulus Probe